

EnkaSonic® 125 A Acoustic Subfloor Solutions

Description	<p>EnkaSonic products have been used for decades in subfloor systems as a medium to address sound control problems caused by airborne and impact noise for building floor systems. Our products combine Enka® technologies along with other</p>	<p>nonwoven technologies to provide proven performance in the construction industry resulting in superior installer-friendly products. Our product range can be customized to meet any requirements or building codes. Our 3D composite design</p>	<p>is ideal for subfloor sound control that addresses impact noise or noise that leaks around the floor at the wall or under the floor/ceiling assembly. The product core is made of polypropylene and fabric attachments are designed with polyester.</p>
Recommended Applications	<ul style="list-style-type: none"> • Multi-Family and Multi-Level commercial constructions • Used under gypsum, concrete, mortar beds, cement backer board or plywood 	<ul style="list-style-type: none"> • With many types of finished floors such as: <ul style="list-style-type: none"> - Laminate Flooring - Tile or Stone - Engineered Wood Flooring 	<ul style="list-style-type: none"> - Sheet Vinyl - Luxury Vinyl Tile (LTV) - Carpets
Features and Benefits	<ul style="list-style-type: none"> • Versatile applications used in most subfloor assemblies for both new and renovation construction • Easy to handle (lightweight and easy to cut) for quick installation • Lightweight rolls and long rolls available 	<ul style="list-style-type: none"> • Quick installation • Custom characteristics and technical properties to meet any requirement • Proven performance as used in thousands of residential buildings and high profile commercial projects (i.e. Coca-Cola 	<p>Headquarters, CBS Studios and MGM Grand Hotel)</p> <ul style="list-style-type: none"> • Used on a variety of subfloors to achieve an STC level of 60+ • Designed to benefit subfloor systems by helping achieve an IIC level of 50+ • UL Certified

Physical Properties	Nominal Thickness (inches)	Nominal Thickness (mm)	Number of Fabrics	Core Color	Nominal Core Width (inches)	Nominal Core Width (m)	Core Weight (oz/d ²)	Core Weight (g/m ²)
	0.13	3	1	Natural	39	1	6	200

TDS- US- EnkaSonic 125 A - 11/20

Packaging

Product	*Roll Length (feet)	*Roll area per Roll (square feet)	# Rolls per Pallet	*Total Area per Pallet (square feet)	Pallet Size
EnkaSonic 250 B	285	926	8 (4X2)	7,410	48"X48"

Availability

Please contact your nearest Sales Office for details

USA T + 1 800 365 7391
The Netherlands T + 31 85 744 1300
China T + 86 519 6858 5555

Quality Assurance
The Quality Assurance System of Low & Bonar has been approved to the ISO 9001 Quality Management System Standard. Certificates are available on request.

Disclaimer
The information set forth in this document reflects our best knowledge at the time of publication. We have a policy of continuous development and therefore our products, information and specifications may be subject to change. We therefore advise you to contact us to make sure the information you receive is accurate and up to date. We don't accept any liability arising from the application of these products, the results thereof or the information given in this document.